

PRODUCT-DETAILS

## 03700320

## 600A 1H AL COMPR LUG 450 STR 550SOL



General Information		
Extended Product Type	03700320	
Product ID	7TAA122010R0019	
EAN	5415022442861	
Catalog Description	600A 1H AL COMPR LUG 450 STR 550SOL	
Long Description	15/25/35kV 600 Amp Series Deadbreak Compression Lug (Tin-Plated Aluminum). Conductor Size kcmil Compressed/Stranded 450 or Compacted/Solid 500/550. Length 5.94 inches. Diameter 1.38 Inches. 1-Hole Pad, .50 inch Thick. Hole Size .688 inch Diameter.	

Ordering	
EAN	5415022442861
UPC	783786650576
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	15 in 381 mm
Package Level 1 Height	8 in 203 mm

Package Level 1 Depth / 19 in Length 483 mm

Additional Information	
Application	Used with 15/25/35kV 600 Amp Deadbreak Elbow and Splice products.
Brand / Label	Elastimold
Cable Size	450 kcmil 500 to 550 kcmil
Color	Silver
Connection Type	Compression
Current Rating	600 A
Effective Date	19980115
Insulation Material	None
Material	Aluminum
Product Name	"electrical connector,>1000v"
Product Type	Compression Lug
Size	Length 5.94 inch, Diameter 1.38 inch, Hole .688 inch Diameter.
Special Functions	Tin Plated Aluminum. Hole Size .688 inch. Connectors can used with both Copper and Aluminum Conductors.
Voltage Rating	15 to 35 kV

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	03700320
Instructions and Manuals	03700320

Classifications	
ETIM 6	EC001053 - Crimp cable lug for aluminium conductors
ETIM 7	EC001053 - Crimp cable lug for aluminium conductors
ETIM 8	EC001053 - Crimp cable lug for aluminium conductors
UNSPSC	39121405
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4532 >> Cable or wire lug

## Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Installation\ Products\ \rightarrow\ Cable\ Accessories\ and\ Apparatus\ \rightarrow\ Cable\ Accessories$ 

03700320 3

