

PRODUCT-DETAILS

## **373J4**

## LB 4-POINT JUNCTION



General Information	
Extended Product Type	37334
Product ID	7TAA121320R0015
EAN	0783786641055
Catalog Description	LB 4-POINT JUNCTION
Long Description	35kV 200 Amp. Loadbreak 4-Point Junction with Stainless Steel Bracket

Ordering	
EAN	0783786641055
UPC	783786641055
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	10 in
	254 mm
Package Level 1 Height	5 in
	127 mm
Package Level 1 Depth /	27 in
Length	686 mm
Package Level 2 Units	40 piece

Additional Information	
Application	Designed for subsurface, vault or padmount applications and can be used for sectionalizing, looping, tapping, and equipment bypass.
Brand / Label	Elastimold
Effective Date	19980115
Material	EPDM Rubber with Stainless Steel Bracket
Product Name	PRIMARY CABLE ACC. 200 SEP CON
Product Type	4-Point Junction
Size	4.00 inch (101.6 mm) Center to Center, 9.6 inch (243.8 mm) High, 3.60 inch (91.4 mm) wide
Special Functions	35kV, 200 Amp Loadbreak 4-Way Junction. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Provides mating for Elastimold Elbow connectors. Mounting hardware for flat or curved mounting positions. Rated for 3 Phase switching. Includes black vent ring.
Standards	ANSI/IEEE 386
Temperature Range	-40 to +65 °C

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	37334	
Instructions and Manuals	373J4	

Classifications	
UNSPSC	26121630
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	1779 >> Cable accessories

## Categories

 $Low\ Voltage\ Products\ \rightarrow\ Cable\ Accessories\ and\ Apparatus\ \rightarrow\ Cable\ Accessories$ 

