

PRODUCT-DETAILS

J4-6226-25

MPJ,4POINT JUNCTION,25KV



General Information

Extended Product Type	J4-6226-25
Product ID	7TAA122020R0127
EAN	0783786241576
Catalog Description	MPJ,4POINT JUNCTION,25KV
Long Description	4 Point Junction, with one 200 Amp Bushing Well Interface, two 600 Amp Bushing interfaces and one 200 Amp Bushing Well Interface, 25kV, No Tilt Mounting.

Ordering

EAN	0783786241576
UPC	783786241576
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
-----------------------	---------

Additional Information

Application	Suited for Subsurface, Vault or Padmount Applications and can be used for Sectionalizing, Looping, Tapping and Equipment Bypass.
-------------	--

Brand / Label	Elastimold
Connection Type	Push-In
Effective Date	20000105
Mounting Type	No Tilt Mounting Bracket.
Product Name	"electrical connector,>1000v"
Product Type	Multi-Point Junction - 4 Points
Size	Overall Length 23 inches, Width 6-3/4 inches.
Special Functions	4 inch Center Spacing.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	J4-6226-25
Instructions and Manuals	J4-6226-25

Classifications

UNSPSC	26121630
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	1779 >> Cable accessories

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

