

PRODUCT-DETAILS

K650SOP

15/25KV 600A DB INSUL PARK BUSHING



General Information	
Extended Product Type	K650SOP
Product ID	7TAA122240R0001
EAN	5415022249507
Catalog Description	15/25KV 600A DB INSUL PARK BUSHING
Long Description	15/25kV 600 Series Deadbreak Insulated Parking Bushing

Ordering	
EAN	5415022249507
UPC	783786652068
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	5.5 in
	140 mm
Package Level 1 Height	3.5 in
	89 mm
Package Level 1 Depth /	8.5 in
Length	216 mm
Package Level 2 Units	1 piece

Package Level 2 Width	45 in
-	1143 mm
Package Level 2 Height	20 in 508 mm
Package Level 2 Depth / Length	43 in 1092 mm

Additional Information	
Application	The Elastimold K650SOP Insulated Parking Bushing is equipped with a 15/25kV class, 600 Amp deadbreak interface, a parking stand and hot stick operable mounting hardware. The K650SOP is inserted into the parking stand with an insulated hot stick and secured in place. Mating Elastimold K655LR/K656LR deadbreak elbows can then be placed on the K650SOP to provide a fully shielded and fully submersible connection. Provisions for grounding the K650SOP mounting bracket are included.
Brand / Label	Elastimold
Effective Date	19980115
Material	EPDM Rubber
Product Name	"ELECTRICAL CONNECTOR,>1000V"
Product Type	Parking Bushing
Size	3.00 inch (76.2 mm) Diameter, 3.88 inch (98.5 mm) Long, 4.82 inch (122.2 mm) Center of Bushing to top of EyeBolt
Special Functions	Fully rated 15/25kV, 600 Amp Deadbreak Insulated Parking Bushing. Allows visible external separation, isolation, and dead-ending. Stainless Steel Bracket. Hot Stick Operable.
Standards	ANSI/IEEE Standard 386

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	K650SOP
Instructions and	K650SOP
Manuals	

Classifications	
UNSPSC	26121630
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	1779 >> Cable accessories

Categories

K650SOP 3

