

PRODUCT-DETAILS

# 274FLR1-C0240

## FUSED ELBOW HOUSING FRCLF



### General Information

|                       |  |
|-----------------------|--|
| Extended Product Type | 274FLR1-C0240  |
| Product ID            | 7TAA124120R0014  |
| EAN                   | 0783786445370  |
| Catalog Description   | FUSED ELBOW HOUSING FRCLF  |
| Long Description      | Molded Current Limiting Fuse Housing, Nominal Fuse Voltage Rating 15.5kV, Fuse Test Port - Two Capacitive Test Ports, Small Housing, Cable Insulation Diameter 0.805 inch - 1.060 inch / 20-27mm, Aluminum Conductor size 1/0 AWG Stranded Compressed, 2/0 AWG Solid Compact |

### Ordering

|                         |                    |
|-------------------------|--------------------|
| EAN                     | 0783786445370      |
| UPC                     | 783786445370       |
| Country of Origin       | United States (US) |
| Customs Tariff Number   | 8535100040         |
| Selling Unit of Measure | each               |

### Container Information

|                        |               |
|------------------------|---------------|
| Package Level 1 Units  | 1 piece       |
| Package Level 1 Width  | 1 in<br>25 mm |
| Package Level 1 Height | 1 in<br>25 mm |

Package Level 1 Depth /  
Length

1 in  
25 mm

## Additional Information

|                     |   |
|---------------------|---|
| Application         | Protect Light Duty Underground Distribution Systems   |
| Brand / Label       | Elastimold  |
| Color               | Black   |
| Current Rating      | 200 A   |
| Effective Date      | 20050113  |
| Includes            | Elbow Connector Housing, Crimp Connector, Probe Lug, Tube of Lubricatn, Installation Instructions, Crimp Chart, V.D. Cap-Peroxide |
| Insulation Material | Yes, EPDM Rubber  |
| Material            | EPDM Rubber   |
| Product Name        | ELECTRICAL FUSE,>1000V  |
| Product Type        | Loadbreak Fused Elbow Connector with Test Point   |
| Size                | Length 16.87 inches from bottom to center of Bushing  |
| Special Functions   | Full-Range Current-Limiting Fusing with 50kA Interrupting Capability. Hotstick Operable 25/28kV Loadbreak Elbow Switching.        |
| Standards           | IEEE 386, ANSI C37.40, ANSI C37.41, ANSI C37.47   |
| Temperature Range   | -40 to +65 °C   |
| Voltage Rating      | 15.5 to 16.2 kV   |

## Certificates and Declarations (Document Number)

|                                   |               |
|-----------------------------------|---------------|
| Data Sheet, Technical Information | 274FLR1-C0240 |
| Instructions and Manuals          | 274FLR1-C0240 |

## Classifications

|                                    |                                       |
|------------------------------------|---------------------------------------|
| UNSPSC                             | 39121421                              |
| WEEE Category                      | Product Not in WEEE Scope             |
| IDEA Granular Category Code (IGCC) | 4586 >> Electrical connector assembly |

## Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

